

CCTV CATALOGUE



PCS
Pacific Cabling Solutions Ltd.



Letter from the President

Pacific Cabling Solutions original goal was to position ourselves as a single source provider of products for those focused in the design and installation of Audio, Video, Voice, Data, Automation and Security Solutions.

With our inception in 2005 we initially provided Wire & Cable along with installation and accessory products such as Low Voltage Mounts, Connectors, Tools and Test products. Since that time, we have continually added new vendors with quality products to each of our product segments in order to complete our portfolio. As a “Customer Driven” distributor, we listen closely to the recommendations and feedback from our customer partners as we go through this vendor and product selection process.

After seven years of compiling some of the best and most recognized names in the industry, many of our customers intimated that our offering within the Security & Surveillance category was lacking. As a result of this valuable feedback, we have promptly responded by aligning ourselves with some exciting up and comers within this market, and have also added new skills and experienced members to our customer care team to ensure you are provided not only with quality products, but staff that will also assist you in design and installation recommendations and solutions.

This short form catalogue is designed to provide you with an overview of our capabilities, for items not listed I invite you to contact one of our customer care professionals.

Sincerely,

Ken Brown



TABLE OF CONTENTS

Cameras – Bullets	3
Cameras – Domes	4
Cameras – PTZ	6
Cameras – SDI	7
Cameras – Day/Night	8
Cameras – Covert/Special Applications	9
Cameras – Box Style & Lenses	11
Monitors	13
Test Monitors	15
NVR / DVR	16
Housing / Mounts	17
Baluns	20
IP Cameras	21
Video Encoders	23
Switches / Midspans	24
IR / Whitelight	26
Microphones	28
Additional CCTV options	29
Contact Information	32





C600BCDN (ARM)
Bullet Camera
600 TVL
3.6 mm
Day/night
12VDC



C600BCDNVF (ARM)
Bullet Camera
600 TVL
3.5 – 16 mm
Day / Night
12 VDC



C653BC2EIRW (ARM)
Bullet Camera
650 TVL
2.8 – 12mm
150 foot IR
Dual Voltage



C600BCIR60 (ARM)
Outdoor Bullet
600TVL
3.6mm
60 fot IR
12 VDC



6305-B (Channel-Vision)
Color Bullet
330 lines
0.5 lux, F2.0
3.6mm lens
Sunshield Included



6026 (Channel-Vision)
Hi Res Waterproof IR Bullet
540 lines
3.6mm 24 IR LEDs 60 ft
3 axis adjustable mount
IP68



ASC-520B21IR-36 (Ascendent)
IR Bullet Camera
520 lines
IP67
12 VDC
21 IR LEDs 50 ft



TV-B110 (Tane)
Outdoor series
420 TVL
4 – 9 mm
24 IR LEDs 30 ft
12VDC / IP65



MLTL2DN49IR/922IR (LIN)
Mini Line Track IR series
540 TVL
3 – axis mounting bracket
Dual Voltage
Split glass tech, no IR reflection



CAMERAS – Dome



C522MDW (ARM)
Color Mini Dome
Indoor
520 lines
3.6mm
12vdc



C650VPWDPRO (ARM)
Vandal Dome
650 TVL
2.8 – 12mm
Day / Night
Dual Voltage



C650VPWDIRPRO (ARM)
Vandal Dome
650 TVL
2.8 – 12mm
90 foot IR
Day / Night



C600MDIRVFW (ARM)
Outdoor Dome
600 TVL
2.8 – 12mm
90 foot IR
Off-White / 12 VDC



6117 (Channel-Vision)
Outdoor Color Vandal dome
550 lines
4 – 9mm lens
Power supply included



6106 (Channel-Vision)
Indoor WDR DNR IR Dome
650 TVL
16x Digital zoom
IR viewing up to 65ft



ASC-420MD-25 (Ascendent)
Indoor Mini Dome
420TVL
2.5mm fixed lens
12VDC



ASC-700EB-2810 (Ascendent)
Vandal Dome
700 TVL
2.8 – 10mm
35IR LEDs 100ft
12VDC



ASC-620MVRD-37 (Ascendent)
Flush Vandal Dome
620TVL
3.7mm Lens
12VDC





ASC-700VRD-2811 (Ascent)
 Vandal Dome
 700TVL
 2.8 – 11mm
 3-axis gimbal
 Dual Voltage



iOne Series (Ascendent)
 iONE-2811 / 3516 / 650-361R
 Featuring 600TVL
 3-Axis Gimbal
 CCVC Capability
 WDR



TV-D100 (Tane)
 Indoor series
 540TVL
 3.5 – 8mm Lens
 12VDC



TV-V30 (Tane)
 Outdoor series
 420TVL
 4 – 9mm vari-focal lens
 12VDC



MLA Series (LIN)
 Mini-line Series vandal domes
 540 TVL
 2.8 – 11mm AI lens
 3-axis
 IP66
 Dual Voltage



D3/D3P Series (LIN)
 Indoor domes
 Quick-install mounting ring
 540 TVL
 2.8 – 11mm lens
 Local bnc test loop
 3-axis bracket



D5 Series (LIN)
 Indoor domes
 Hi Res 540TVL
 2.8 – 11mm lens
 WDR option
 Plenum rated backbox option





Flex-10X-IN (Ascendent)
Indoor
10X Zoom
36IR LEDs
12VDC
480TVL



ASC-600PTZ-37X (Ascendent)
Outdoor
37X Optical Zoom
Hi Res 600TVL
16X Digital Zoom
Integrated WDR



FLEX-37X (Ascendent)
Outdoor
Infrared or Laser Infrared
Illumination
480 TVL Resolution
IP 65 Weatherproof



PTZA6-1 Series (LIN)
Indoor
6-inch PTZ Dome
23X / 30X / 35X zoom options
D/N Operation
Pendent / Wall Options



PTZA6-2 Series (LIN)
Outdoor Use
6-inch PTZ Dome
23X / 30X / 35X zoom options
D/N Operation
Pendent / Wall Options





ASC-SDI2MP-BOX
(Ascendent)
2MP HD-SDI Box Camera
Day/Night
Dual Voltage
Wide Dynamic Range



ASC-SDI2MP-D-2810-40IR
(Ascendent)
2MP HD-SDI Dome Camera
40IR LEDs
Dual Voltage
2.8 – 10MM vari-focal



ASC-SDI2MP-VRD-2810
(Ascendent)
Vandal Resistant SDI Dome
2 MegaPixel
Day/Night
2.8 – 10mm Varifocal



SC-SDI2MP-VRD-2810-40IR
(Ascendent)
2MP SDI Vandal Resistant IR Dome
Day/Night
40IR LEDs (60°)
Dual Voltage
IP068



ASC-SDI2MP-B-2810-80IR
(Ascendent)
2MP HD-SDI Bullet Camera w/IR
Day/Night
80IR LEDs
Day/Night
2.8 – 10mm Varifocal



ASC-SDI2MP-10X
(Ascendent)
10X Zoom SDI Camera
16X Digital Zoom
Wide Dynamic Range
OSD Programming





OCD25XSD (Arm)
Outdoor Day/Night PTZ
25x optical zoom
480 lines
24VAC



C600MDVPDN (Arm)
Mini Dome
600 TVL
3.6 mm
Day / Night
12 VDC



C650VPWD (Arm)
Day / Night Dome
650 TVL (750 b/w)
Wide Dynamic Range
2.8 – 12mm
3 – Axis
Dual Voltage



C653BC2EW (Arm)
Day/Night Bullet
2.8 – 11mm
540 lines
Dual voltage
IP66



VIS-48IR-2910 (Ascendent)
110ft IR Day/Night Camera
2.9 – 10mm lens
550 TVL
48 IR LEDs
IP67
Dual Voltage



AP-650-2812 (Ascendent)
Easy Install IR Day/Night Camera
600 TVL
2.8 – 12mm Lens
Wide Dynamic range
65 IR LEDs
Dual Voltage



AP-101IR-550 (Ascendent)
295ft IR D/N Camera
550 TVL
5 – 50mm lens
101 Infrared Bulbs
IP67
24VAC



AP-550IR (Ascendent)
500ft IR D/N Camera
540TVL
5 – 50mm Lens
35 Infrared Bulbs
IP67
24VAC





C520HDCVFIR492ACTD
(Arm)
IR Heavy Duty Cameras
520 Lines
5 – 50mm lens
492-foot IR Range
12VDC or 24vVAC / IP66



C542SDCS (Arm)
Smoke Detector Camera
Color
540 Lines
3.7 mm
12 VDC



C542PIR (Arm)
PIR Camera
Color
540 Lines
3.7 mm
12 VDC



C600MCDN (Arm)
Hi Res Metal-Cased Camera
520 Lines
3.6mm Lens
12VDC



6403 (Channel-Vision)
Hi Res Mini Pinhole Color camera
550 TVL
5.5mm Lens
1" x 1" ultra compact design
Power supply included



6200-212 (Channel-Vision)
Single-Gang Color Box Camera
550 TVL
Includes Power Supply
Fits into Standard Gang Box
Adjustable Mount



6404 (Channel-Vision)
WDR Hi Res Camera
560 TVL
5.5mm Lens
Wide Dynamic Range



ASC-380PIR-37-MD (Ascendent)
Covert Proximity Detector Camera
Motion-Activated Camera
Stand alone or alarm system
380TVL
3.7mm lens
12VDC



ASC-420MIR-4 (Ascendent)
Covert mirror Camera
420TVL
4mm lens
12VDC





ASC-SUB20M-6 (Ascendent)
Submersible Camera
30m cable lead and remote
540 TVL
8 White light LEDs
12VDC



AP-550IR-LP (Ascendent)
License Plate Camera
Day/Night
540 TVL
35 Infrared Bulbs
5 – 50mm Varifocal
IP67 / 24VAC



ASC-540PTZ36X (Ascendent)
Rugged PTZ
Made from Aluminum alloy
With or without Illumination
Explosion Proof
Ideal for high level security



VAD-IR (Ascendent)
Rugged Laser IR PTZ
Optimized for long range security
ZLID Illumination
Precision Optics
37X Zoom Lens / 16X Digital Zoom



AZCCTV701 (Azco)
Auto-Tracking Day/Night Camera
180 degree motion tracking
12VDC
White



AZCCTV701C (Azco)
Auto-Tracking Day/Night Camera
180 degree motion tracking
Outdoor
12VDC
Black



LPRS Series (Illum)
License Plate Recognition Camera
Captures plates at speeds of up to 30MPH
Capture Range up to 60 feet
No motion blur
24VDC/AC



HC1CH30 (LIN)
Height Strip Camera
540 TVL
3.0mm lens
12VDC
Covers 4' to 6 1/2' heights



SC1CH36-B (LIN)
Sign Camera
3.6mm lens
Adjustable mounting bracket
12VDC
Black



CAMERAS – Box Style



C600DN (ARM)
True Day/Night Security Camera
Color 600 Lines
Day/Night
Night Lux Rating 0.01@F1.4
Dual Voltage Power (300ma)



6500 (Channel-Vision)
Color Box Camera
Color 380 Lines
3.3 – 12mm vari-focal Lens
Power supply included



ASC-540CC (Ascendent)
Simple True Day/Night
Color 540 Lines
Day/Night
Dual Voltage
On Screen Display (OSD)

LENSES

Ascendent Features:

*1/3" Format
CS Mount
Manual or Auto Iris Models
All Glass Elements
Low F Rating*



Manual Iris

L-2812MI	2.8 – 12mm
L-358MI	3.5 – 8mm
L-6	6mm
L-615MI	6 – 15mm
L-2812F13	2.8 – 12mm



Auto Iris

L-2812AI	2.8 – 12mm
L-615AI	6 – 15mm
L-660	6 – 60mm



ARM Electronics Features:
1/3" Format
CS Mount
Manual or Auto Iris Models
All Glass Elements
Low F Rating



VL2812MI
Manual Iris
2.8 ~ 12mm



VL550AI
Auto Iris
5 ~ 50mm



VL2812ASIR
Auto Iris
2.8 ~ 12mm



VL2812AI
Auto Iris
2.8 ~ 12mm



VL5100AS
Aspherical Auto Iris
5 ~ 100mm



VL850ASIR
Auto Iris
8 ~ 50mm



VL615AI
Auto Iris
6 ~ 15mm



MONITORS



B/W Monitors (Arm)
Tube
9" / 12" / 14"
High resolution 1000 lines
Looping BNC
Looping Audio



Color Monitors (Arm)
Tube
14" / 21"
High Resolution 500 lines
Looping BNC
Looping Stereo RCA



LCD Value (Arm)
15" / 20"
VGA / BNC input
Vesa Compliant



LCD Standard (Arm)
15" / 17" / 19"
Vesa Compliant
VGA/BNC/S-video
OSD Control



ASC-22WLCD (Ascendent)
22" LCD Monitor
16:9 widescreen
Full HD Res 1920x1080



TM Series (Tatung)
Economic LCD Monitor
17" to 42"
HDMI / BNC / VGA inputs
4:3 and 16:9 Aspect ratio



TLM-06T Series (Tatung)
15" / 17" / 19"
Energy Efficient
BNC Loop Thru
High Brightness



TLM HD Series (Tatung)
Full HD 1080P LCD Display
32" / 42"
24/7 Commercial Grade
High Contrast



MONITORS



TLTM19AD (Tatung)
19" LCD Touch Monitor
5 wire resistance
USB & RS-232 Interface
Rack Mountable



SM17P-B (LIN)
17" LCD Security Monitor
1280x1024 @60Hz Res
VGA / BNC Inputs
Vesa Mounting



SM19P-B (LIN)
19" LCD Security Monitor
1280x1024 Resolution
Looped BNC inputs
VGA input



TEST MONITORS



4SMKIT (Arm)
4" LCD Service Monitor
Resolution (480 x 234)
Looping BNC
Weight (0.7LBS)



56SMKIT (Arm)
5.6" LCD Monitor Kit
Dual Video Inputs
Resolution (960 x 234)
Weight (2.1LBS)



MON-35WM (Ascendent)
3.5" Screen
Wrist Monitor
Weight (1.6LBS)



TLM-0271 (Tatung)
2.7" Screen
Sunlight Readable
Resolution (320 x 240)



AZLM401 (Azco)
Lightweight
Hands free
Built in rechargeable battery



TV-700 (Tane)
7" TFT LCD
Weight (3.3LBS)
16:9 and 4:3 aspect ratio



Video-330 (Tane)
2.5" LCD Screen
Resolution (960 x 240)
Control PTZ Function
On-Screen Display



CAM-SUT1 (LIN)
3.5" LCD Screen
PTZ Control
RS485 data Capture
Weight (0.8LBS)





HR Series (Arm)
H.264 Compression
Up to 240 FPS Recording
IR Remote Control
Mobile View Software



DVR-C Series (Channel-Vision)
H.264 Compression
SATA Hard Drives
Mirror recording of drives.
Remote Viewing



DVR-43G Series (Channel-Vision)
3G Compatibility
IR Control
MAC Compatible
H.264



DVR-163G Series (Channel-Vision)
Dual Streaming
H.264
Picture in Picture
3G / GPRS



X4 Mini (Ascendent)
Up to 16 D1 Channels
Up to 2TB Storage
HDD or SSD OS Drive options
Upgradable to a Intel Core i7



X4HD DVR (Ascendent)
Up to 16 SDI Channels
record 30FPS @1080P
resolution
HDD or SSD OS Drive options
Upgradable to a Intel Core i7



X4 DVR (Ascendent)
Up to 64 D1 Channels
Rack Mountable
Up to 8TB Storage
Upgradable Add 4 channels of
HD-SDI



USB Series (Ascendent)
Up to 16 CIF Channels
Up to 2TB storage
A 24/7 Turnkey Solution



X4S-DVD Series (Ascendent)
Up to 16 D1 Channels
Up to 4 TB storage
USB / DVD Backup
H.264





VPPROWMT (Arm)
Heavy Duty Mount
Cable Management
For use with VPPRO Series



OCH Series (Arm)
Standard Housing
Heater/Blower Option
Cable Management Option



OCHWMT (Arm)
Wall Mount
Heavy duty
360 Swivel Angle



CWMP (Arm)
Beige Plastic
90 Tilt Angle
Wall Mount



MCM6 / 6W (Arm)
Black / Beige
Metal Dual Mount
360 Swivel Angle



FLC430 (Arlington)
Cam-Box Kit
Up to 50 LBS Ceiling
Easy install with 4-inch hole.



8161TR (Arlington)
UV Rated for long life
Matches Standard 4-inch box
10 LBS wall / 50 LBS Ceiling



8161CB (Arlington)
UV Rated for long life
Matches Standard 4-inch box
50 LBS Corner Mount



M-PM (Ascendent)
Pole Mount
White





ASC-1316M-BLK (Ascendent)
Universal Mount
Black



ASC-8120 (Ascendent)
IR Housing
Compact
White



ASC-1315HB (Ascendent)
Camera Housing
Outdoor
White



OMT10.0 (Omnimount)
Fits most large CCTV Cameras
Supports up to 10 LBS
360 rotation
Black or White



HS91 (LIN)
TEC Series Housing
Includes Sunshield
27-inch Length



HS9305 (LIN)
High Security
Indoor
15-inch Ceiling/Wall Wedge



HS9303 (LIN)
High Security
Indoor
Corner Housing



HS9405 (LIN)
High Security
Compact Design
11-inch Wall/Ceiling Wedge



MT9213 (LIN)
Pole Adapter
Lightweight
Corrosion-resistant finish





MT9215 (LIN)
Feed-Thru Mount
Medium Size
Corrosion-resistant finish



MT9210 (LIN)
Column Mount
Medium Size
Corrosion-resistant finish



FS420SCL (Arlington)
Steel Fixture Box for Suspended
Ceilings
Comes preset for 24-inch grid
Rated for 50 LBS



BALUNS



BLN-BNCJ (GEM)
BNC Jack to RJ45 Jack
Cat5E = 2200FT



BLN-BNCJKS (GEM)
BNC Jack to RJ45 Jack
Keystone Type
Cat5E = 2200FT



BLN-PVRJ45-1 (GEM)
Power-thru Type Video
and Power
680 Meters – Video
Max Current Rating 4.5A
(AC RMS/DC)



BLN-TL (GEM)
BNC Plug to Toolless
Cat5E = 2200FT



BLN-MTL2 (GEM)
Screw Terminal
Space Savers



BAL-P10 (Ascendent)
Cat5E = 1300FT
Terminal Connection



AZBLN210 (Azco)
1 Ch Passive
1500FT on Cat5E
Sold in Pair



AZBLN201 (Azco)
1 CH Passive
1000Ft on Cat5E
Sold in Pair



AZBLN204 (Azco)
1CH Passive
1000Ft on Cat5E
One pigtail / One Mini





CAM-13DN-IP (LIN)
 1.3 Megapixel
 Indoor
 Day/Night
 12VDC/24VAC
 POE



CAM-30DN-IP (LIN)
 3.0 Megapixel
 Indoor
 Day/Night
 12VDC/24VAC
 POE



X4-IP-MINI (Ascendent)
 VGA Res (640x480)
 Standard H.264
 Power supply included



NTL-10DN-312 (LIN)
 1.0 Megapixel
 Outdoor Use
 POE
 IR LEDs for Zero-Lux Illumination
 3.3 – 12mm Varifocal Lens



6522 (Channel Vision)
 2 Megapixel
 Outdoor Use
 H.264 Compression
 35 IR LED approx 60FT
 2-way Audio



X4-2MP-WIR (Ascendent)
 2 Megapixel
 Outdoor Use
 Wireless
 46IR LEDs
 Advanced H.264



X4-IP-540-36IR-WP (Ascendent)
 540TVL
 Outdoor Use
 Day/Night
 36IR LEDs



ND4/5 Series indoor (LIN)
 1.3 Megapixel
 Various Mounting Options
 POE 802.3af
 3.3 – 12MM Varifocal Lens
 2 way audio
 Local Storage Capability



IP CAMERAS



ND3/4 Series Outdoor (LIN)
1.0 / 1.3 Megapixel Resolution
POE 802.3
Aluminum casing



6521 (Channel Vision)
2 Megapixel
IP66 Rated
3-Axis Bracket
18 IR LED
3G Live



X4-IPD-359 (Ascendent)
4CIF Resolution
POE
Internal SD card slot
H.264
3.5 – 9mm Varifocal



X4-2MPD-2811 (Ascendent)
Indoor
2 Megapixel Resolution
POE
MPEG4 Compression
2.8 – 11mm Varifocal



X4-PTZ-18X-HD (Ascendent)
HD Rugged Outdoor
1.3MP
18X Zoom from Lens
12X Digital Zoom
IP66 Weatherproof



VIDEO ENCODERS



ENC-D1POE (LIN)
D1 Resolution
Built in mic
BNC Output
Two-way Audio



W-1001 (Channel Vision)
1 Channel Input
H.264/MJPEG/MPEG4
Compression
2-way audio
Supports Cell / PDA / 3GPP



W-4001 (Channel Vision)
4 Channel Input
H.264/MJPEG Compression
SD Card backup
2-way Audio



X4-1 (Ascendent)
1 Channel Video Sever
True "Plug and Play"
H.264



X4-4 (Ascendent)
4 Channel Video Sever
True "Plug and Play"
H.264



X4-1 w/ internal HDD
(Ascendent)
4 Channel Video Sever
True "Plug and Play"
H.264
Internal HDD



X4-4 w/internal HDD
(Ascendent)
4 Channel Video Sever
True "Plug and Play"
H.264
Internal HDD





C-0531 (Channel Vision)
Data/Patch 8-port Switch
Double decker mounting plate
Two 8x8 network hubs
One 8 port switch



C-0558 (Channel Vision)
8 Port Gigabit Ethernet Switch
Auto MDI/MDI-X on each port
EEE802.3x Compliant
Designed for plug and play



C-0538 (Channel Vision)
CAT6 Data Patch Panel
110 punchdown / RJ-45 connections
Ideal for Hi Bandwidth Video Streaming
Compatible with CAT5 / 5E / 6



C-0526 (Channel Vision)
4 Port Wireless Router
Hi Speed wireless N Connectivity
Up to 4 multiple SSIDs
Advanced security



C-0532 (Channel Vision)
Data/Patch 8-port switch
Two 8 port CAT6
Data Termination Hubs
One 8 port Switch
One Universal Holder



AZPOE3500 (Azco)
Power over Ethernet
Delivers Voice, Data and POE



AZEPOE1 (Azco)
Easy POE passive injector
Distance based on power supply
Great for analog to IP conversions



AZIPO3 (Azco)
IP Extender
Extends any TCP/IP device
Up to 4000ft



WHR-HP-G300N (Buffalo)
802.11b/802.11g/802.11n
Up to 150 MBPS (1x1)
Up to 300 MBPS (2x2)
DD-WRT with Hi Power Tech





WZR-HP-AG300H (Buffalo)
802.11b/802.11g/802.11n
Simultaneous Dual-band
DD-WRT with Hi Power Tech
Gigabit Ethernet
USB Storage Port



WLAE-AG300N (Buffalo)
Dual Band wireless
Ethernet converter
Access point and bridge
Connect any two wired devices
to an existing Network
802.11n Dual Band support



**LinkStation Series
network Storage** (Buffalo)
1 / 2 / 4 drive solutions
PC and Macs
Up to 8TB storage and Raid
Cost-effective solutions



**Terastation Series
network storage** (Buffalo)
Premier network storage
(NAS) Network attached storage
(SAN) iSCSI storage area network
Raid, hot-spare and real-time replication



Cloudstor series storage
(Buffalo)
Personal cloud storage)
Offers terabytes of storage
Access anytime anywhere from
PC, Tablet and Smartphones
No fees



BS-G2124U (Buffalo)
24-port rackmount gigabit switch
Plug and play set up
Auto-MDIX ports
Fast gigabit speeds
Available in 16 port option



BS-2116U (Buffalo)
16-port SMB 10/100 Switch
Plug and play set up
Auto-MDIX ports
Monitored power to ports
Loop detection
Available in 8 port option





R919 Series (Illum)
 Super Long Range IR
 Distances up to 919'/280m
 Angles 10°/30°/60°/100°
 IP67 weatherproof
 Built-in photocell IR on/off



IR623 Series (Illum)
 Long Range IR
 Distances up to 623'/190m
 Angles 10°/30°/60°/100°
 IP67 weatherproof
 Built-in photocell IR on/off



IR312 Series (Illum)
 Medium range IR
 Distances up to 312'/95M
 Angles 10°/30°/60°/100°
 IP67 weatherproof
 Built-in photocell IR on/off



IR148 Series (Illum)
 Short range IR
 Distances up to 148'/45m
 Angles 10°/30°/60°/100°
 IP67 weatherproof
 12-32VDC or 24VAC input



POE Series (Illum)
 Provides dedicated lighting for IP cameras via PoE+
 IEEE802.3af Compliant
 Distances up to 312' (95m)
 850nm or 940nm Wavelengths
 SMT LED technology



IR148-POE Series (Illum)
 Provides dedicated lighting for IP cameras via PoE+
 IEEE802.3af Compliant
 Distances up to 115' (35m)
 Angles 10°/30°/60°/100°/120°
 850nm wavelength



5040 (Channel Vision)
 IR Illuminator
 Waterproof/ Outdoor use
 33 feet distance
 Built-in Light sensor activation



WL100 Series (Illum)
 Short range white light illuminator
 Distances up to 165'/50m.
 Energy efficient (7W max.)
 Compact and stylish
 12Vdc/24VAC power input



WL105-POE Series (Illum)
 Provides dedicated lighting for IP cameras via PoE
 Distances up to 82' (25m)
 IEEE802.3af Compliant
 SMT LED technology
 IP67 weatherproof





WL220-POE Series (Illum)
provides dedicated lighting for IP cameras via PoE
Distances up to 220' (67m)
IEEE802at Compliant
SMT LED technology
IP67 weatherproof



WL436 Series (Illum)
Long range white light illuminator
Distances up to 436'/133m
Visible light for color CCTV cameras
Low power consumption (39W)
12-32VDC or 24VAC input



WL643 Series (Illum)
Super long range white light illuminator
Distances up to 643'/196m
Low power consumption (52W)
Built-in photocell IR on/off
12-32VDC or 24VAC input



WL860-ST (Illum)
Designed for street lighting, parking lots, industrial sites.
Energy Efficient (150W max.)
Replaces high/low pressure sodium and mercury lamps
140deg. angle light distribution





WM-625/WM-625S (Astatic)
 Indoor omni-directional wall mount microphone
 Frequency response tailored for crisp, clear speech
 Push-To-Talk option (DPDT switch)



220VP (Astatic)
 RF Resistant Continuously-variable Pattern Condenser
 Continuously-variable polar pattern control
 All-metal housing suitable for commercial applications



201R (Astatic)
 RF Resistant Cardioid Condenser Mini-Boundary Mic
 RF resistant design
 Low profile mounting
 Hemi cardioid directional
 13/16" (20mm) threaded diameter with mounting hardware



202RW (Astatic)
 RF Resistant Omni Condenser Mini-Boundary Mic
 RF resistant design
 Low profile mounting
 Hemi omnidirectional pick-up pattern



5104-MIC (Channel Vision)
 Add audio to any camera
 Line level outputs
 12VDC @ 200 MA
 Simple RCA connection



TSD-ML11 (Atlas)
 1 x 1 Mic/Line Preamp
 Switchable 24v Phantom Power
 Variable Output Limiter/Compressor
 Security covers included



TSD-ML22VCA (Atlas)
 2 x 2 Mic/Line Preamp and VCA
 True VCA for remote Volume Control
 Switchable 24v Phantom Power
 High gain outputs for distance





PTZA6X (LIN)
Pan-Tilt-Zoom Accessories
3-Axis Joystick
Corner / Pole / Wall Mount
Rail support Kits



PT9418 (LIN)
Medium Duty Pan/Tilt Series
Max Load – 22lbs (10 kg)
Feed-through wiring available
100% duty cycle motors



SCX-RD100 (Ascendent)
iONE Controller
Coaxial Remote configuration
Fir the iONE series cameras



PTZ-3X-CON (Ascendnet)
3-Axis PTZ Controller
Pelco D protocol



PB series power supply
(Ascendent)
PB-1812VDC-10A 18 Ch 12VDC
PB-912VDC-5A 9 Ch 12VDC
PB-412VDC-2A 4 Ch 12VDC
PB-1824VAC-10 18 Ch 24VAC
PB-924VAC-5A 9 Ch 24VAC



PS Series Power supply
PS-12VDC-1000 12VDC 1000ma
PS-12VDC-2A 12VDC 2000ma
PS-12VDC-5A 12VDC 5000ma
PS-12VDC-2000-4X 12VDC 4 Ch
PS-24VAC-2000 24VAC 2000ma
PS-24VAC-3000 24VAC 3000ma



H16P-RJ45 (GEM)
CCTV Patch Panel
Low profile
Mounts in standard 19" rack



H16P-RJ45BNC-2 (GEM)
CCTV Patch Panel
Low Profile
2-wire PTZ Control



GLI-BNCPJPT-1 (GEM)
Ground Loop Isolator
Male BNC to Female BNC



ADDITIONAL CCTV OPTIONS



SP-BNCPJ (GEM)
Surge Protection
Multiply BNC Connector options



GP100 (Ascendent)
Ground Loop Isolator Twisted Pair to BNC



TK-CT2-CAM-BNC (TPS)
Security Camera Protection
Surge Protection
Fail-Safe design
Allows two way communication



TK-CT2-CAT5E (TPS)
Ethernet CAT5E Protection
Cat5 data lines (1GBPS max)
Surge Protection
POE version available
Fail-safe design



TK-TTLP-1S240-FL (TPS)
Breaker Panel placement
Surge Suppression
Power Filtering
120/240 Split Phase
3W+G



CSP1 (ARM)
Coaxial Surge Protection
100ns surge protect attack time
5amp max. surge current
Surge life 300 surges



DA14 (ARM)
1 in / 4 out video
1000 range
Power supply included



VCR30RT960J (ARM)
Time Lapse VCR
30 hrs real-time
960 hrs time-lapse
Time/date display
Wireless remote



VCR800 (ARM)
Casino VCR Recorder
8 hours real-time
Half size design
3 record modes





SDKBD Series (ARM)
PTZ Controllers
SDKBD1 Basic Control
SDKBD2 Full Function
SDKBD3 w/ 3-Axis joystick



6014 (Channel Vision)
Camera Sequencer
4 input / 2 output
Cat5e connection option avail.
with 6210 camera (sold separately)
Cat5e breakout option for
standard camera with 3112
(sold separately)



MMS-PTZ-BNC (Minuteman)
LineGuard series
Surge Suppressor
For analog cameras
BNC Connection for video
Terminal block for power



MMS-CAT5-POE-RJ45
(Minuteman)
LineGuard series
Surge Suppressor
For CAT5 LAN/POE lines
Uses RJ-45 connectors
For Lan and POE protection



EN400/EN600 (Minuteman)
Enspire standby UPS series
USB Communication
RoHS Compliant
Larger Load Capacities



EN750/EN900 (Minuteman)
Enspire standby UPS series
LCD Display
Coaxial Cable protection
More Outlets



CONTACT INFORMATION



Business Hours:

8:00am to 4:30pm Monday through Friday

British Columbia Branch & Head Office

Pacific Cabling Solutions Ltd.

#19 – 7163 Vantage Way

Delta, British Columbia, Canada V4G 1H1

Telephone: 604.946.0669 Toll Free: 1.800.946.0669

Fax: 604.946.0609

Sales: customercare@pacificcabling.com

Administration: admin@pacificcabling.com

Employment: careers@pacificcabling.com

Alberta Branch Office

Pacific Cabling Solutions Ltd.

#12 3140 14th Avenue NE

Calgary, Alberta, Canada T2A 6J4

Telephone: 403.248.0669 Toll Free: 1.888.504.0669

Fax: 403.248.0609 Email: calgary@pacificcabling.com

Manitoba Sales Office

Armas Sales

1654 St. James Street

Winnipeg, MB Canada R3H 0L3

Telephone: 204.775.2702 Email: armas@mts.net

Ontario Sales Office

Pacific Cabling Solutions Ltd.

7 Strandmore Circle

Brooklin, ON L1M 0C1

Telephone: 416.892.1197 Email: msouth@pacificcabling.com

Quebec & Atlantic Canada Sales Office & Warehouse

CR3 Media

Media 1004 Route 105

Chelsea, QC Canada J9B 1P3

Telephone: 514.871.1212 Email: crobertson@cr3media.com

