

Toll-Free (800) 323-9355

Wiring The World

Fax: (847) 689-1192

PRODUCT PURCHASING SPECIFICATION

 PART NUMBER:
 97194

 DESCRIPTION:
 24/2PR +16/2 CL2R CABLE

 CONSTRUCTION:
 This cable consists of 24/2 pair and 16 AWG two insulated conductors with an overall PVC jacket

 APPROVALS:
 ETL Listed to UL Standard 13

Construction Parameters:

Conductors	24ga:	24 AWG Solid BC
Insulation (Polyethylene)	16ga: 24ga:	16 AWG 19/.0117" BC 0.008" Nom.
	16qa:	0.008" Nom.
Insulated Cond. Dia.	24ga:	0.036" Nom.
	16ga:	0.072" Nom.
Number of Conds.	24ga:	4 (2 twisted pairs)
	16ga:	2
Lay Length		24ga varied lengths of pairs, 16ga run parallel under jacket
Overall Jacket Material		PVC
Overall Jacket Thickness		0.017" Nom.
Overall Cable Diameter		0.185" Nom.
Approximate Cable Weight		33.9 Lbs/1M' Nom.
Flame Rating		UL 1666 Riser Flame Test

Electrical Properties:

Temperature Rating Operating Voltage -20[°]C to 60[°]C 300 V RMS Max.

16/2: Red Wht

24/2pr: Wht/Blu Wht/Org

Component Colors

Jacket Color

Legend (Surface Ink Print)

COLEMAN CABLE 24/2PR + 16/2 (ETL) ETL# TYPE CL2R

White (Other colors available, please consult factory)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

Material is not returnable and purchase order is non-cancelable after production has been started or special materials have been ordered.

The information presented here is, to the best of our knowledge, is true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name_____ Date Signed _____

Customer Approval _____

Specification Issue Date: April 9, 2003