

1281S3 Coax - Banana Peel® Unjacketed Bundles Mini Hi-Res Component Video

Number	Color
1	Red
2	Green
3	Blue

OVERALL CABLING:

Overall Cabling Fillers	Bonded Spline
-------------------------	---------------

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	Unjacketed
-----------------------	------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.246 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +75°C
UL Temperature Rating	60°C
Non-UL Temperature Rating	75°C
Bulk Cable Weight	44 lbs/1000 ft.
Max. Recommended Pulling Tension	90 lbs.
Min. Bend Radius (Each Coax)	1.1 in.
Min. Bend Radius (Overall)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	02/24/2005

FLAME TEST:

UL Flame Test	UL1666 Vertical Shaft
---------------	-----------------------

SWEEP TEST:

Sweep Testing	5 - 850 MHz
---------------	-------------

SUITABILITY:

Suitability - Indoor	Yes - Risers
Suggested Connectors	ADC - BNC-16; KINGS - 2065-25-9; TROMPETER - 105-2053-0; BELDEN 1B25A (BNC); BELDEN 1R25A (RCA)

PLENUM/NON-PLENUM:

1281S3 Coax - Banana Peel® Unjacketed Bundles Mini Hi-Res Component Video

Plenum (Y/N)	N
Plenum Number	1282S3, 1277P

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	.087 μ H/ft
Nom. Capacitance Conductor to Shield	17.0 pF/ft
Nominal Velocity of Propagation	80 %
Nominal Delay	1.24 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	34 Ohms/1000 ft
Nom. Inner Shield DC Resistance	5.4 Ohms/1000 ft

Minimum Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Return Loss (dB)
		5	850	20

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			0.52
	5			1.17
	50			3.7
	100			4.9
	200			6.7
	400			9.5
	750			13.4
	900			15.0
	1000			15.8
	3000			31.2

Max. Operating Voltage - UL	300 V RMS
Max. Operating Voltage - Non-UL	300 V RMS

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1281S3 0001000	3C25 RGB	1000	29	NONE	C
1281S3 000500	3C25 RGB	500	15.5	NONE	C

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 12-19-2005

1281S3 Coax - Banana Peel® Unjacketed Bundles Mini Hi-Res Component Video

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.