ONE-BOX™ Non-metallic Outlet Boxes

Thore on

The Versatile Outlet Box for New or Old Work









ONE-BOX[™] includes ground clip for CSA Listing

Fast and easy to install, Arlington's versatile outlet box is the **ONE-BOX™** for new or old work. Suitable for a variety of wall thicknesses, ONE-BOX is removable, adjustable and reuseable – even after the wall is in place.

Angled Robertson head screws inside the ONE-BOX mount it securely to a wood or steel stud. There are no mounting wings so there is no wobble.

NEW WORK

ONE-BOX set too far forward or back?

Just back out the screws

and readjust.

OLD WORK

ONE-BOX mounts to the stud, not just the drywall.

- Extra-large cubic inch capacity
- Horizontal and vertical single gang and multiple gang styles
- UL Listed in the U.S. and Canada
- For power and low voltage applications with the F102D voltage separator installed
- Includes ground clip
- Two-hour fire rating



1 Stauffer Industrial Park Scranton, PA 18517


800/233.4717 Fax 570/562.0646 www.aifittings.com

ONE-BOX™ Non-metallic Outlet Boxes

Secure Installation • Mounts directly to a wood or steel stud

F102GC 2-gang

(Supplied NM cable connectors and blanks) Combination 1/2", 3/4" knockout on back (not visible)



Patented. Other patents pending.





1 Attach ONE-BOX to wood or steel stud with captive Robertson head installation screws. If box is too far forward or back, back the screws out and reposition it.




2 Pull wire through supplied NM cable connector.



1 Position ONE-BOX next to stud. Use box as the template to cut hole.



2 Pull wire through NM cable connector (supplied). Insert ONE-BOX.



3 Mount ONE-BOX directly to stud with shipped in place Robertson head screws.





F101HGC

CATALOG NUMBER	UPC/DCI/NAED MFG #01 8997	DESCRIPTION Non-metallic Outlet Box	CUBIC INCHES	UNIT PKG	STD PKG
F101GC	37950	Single-gang, vertical	21.3	50	50
F101HGC	37951	Single-gang, horizontal	22.5	25	25
F102GC	37952	Two-gang, vertical	40.0	25	25
F103GC	37953	Three-gang, vertical	61.0	25	25
F104GC	37954	Four-gang, vertical	78.0	10	10
Robertson head installation screws ship captive. Supplied NM cable connectors, blanks and ground clip.					
F102D	43544	Voltage Separator	N/A	25	25





1 Stauffer Industrial Park Scranton, PA 18517

800/233.4717 Fax 570/562.0646 www.aifittings.com



F101GC 1011/10M





F102D

Distributed by