

MMKVM17NB2RR - Dual rail 17-inch LCD monitor
MMKVM15NBSR - Single rail 15-inch LCD monitor



Front view of KVM 17-inch dual-rail rackmount LCD console [MMKVM17NB2RR]



KVM 17-inch dual-rail rackmount LCD console in open position. User can slide keyboard back into rack leaving LCD screen visible. (See photo on left)

The Minuteman[®] 17-inch dual-rail rackmount LCD console is ideal for any rackmount environment providing excellent resolution, brilliant colors, easy installation and operation. The user has the unique ability to view the display with the keyboard and mousepad retracted. The unit occupies only 1U of rack space.

- **Unique design** - The dual-rail design of the monitor permits the PS/2 keyboard and mousepad to be retracted into the rack leaving the LCD monitor flush with the front of the rack and the display visible. The drawers move independently of each other enabling casual monitoring of connected systems without a protruding keyboard. Occupying only 1U of rack space, the dual-rail design provides the ultimate convenience for IT personnel and network administrators to control and monitor data center or server devices.
- **Rugged construction** - The LCD console system is made with heavy gauge sheet metal offering protection against accidental dents, damage and vibrations.
- **Advanced screen design** - The LCD screen has a positive tension hinge that enables you to place the monitor at any angle for viewing. Its bright active matrix 17-inch TFT LCD-display is protected by tempered glass.

- **Display controls** - Convenient controls provides adjustments for auto tuning, brightness, contrast, color and image position for the video display. The ability to display the menu in English, German, French, Italian and Spanish further enhance the flexibility of the console.
- **Ideal for interfacing with KVM systems** - The MMKVM17NB2RR is designed to work with any KVM (keyboard-video-mouse) system. A floating OSD (on-screen-display) function, when used with Minuteman KVMs, provides a visual status of the KVM-connected components. Internal firmware provides the ability to use shortcut "hot keys" for entering commands.
- **Two-year warranty** - Includes parts and labor (in U.S.A. and Canada only).

Specifications

Item	Description
LCD size	17-inch TFT active matrix
Resolution	1280 x 1024 (SXGA)
Pixel pitch	0.264mm x 0.264mm
Display colors	16.2 million – true color
Brightness	250 cd/m ² typical
Viewing angle	140 degree H x 120 degree V
Contrast ratio	450:1 typical
Keyboard	105 Key PS/2 notebook keyboard with integrated touch pad & window key
Numeric key pad	Yes
Dimensions - closed	19.0in x 19.6in x 1.9in (482.6mm x 497.8mm x 48.3mm)

Minuteman® KVM 15-inch single-rail rackmount LCD console with keyboard and mouse



Front view of the Minuteman® KVM 15-inch single-rail rackmount LCD console

[MMKVM15NBSR]

The economical Minuteman® KVM 15-inch single-rail rackmount LCD console with keyboard and mousepad is ideal for installation in a rack with Minuteman and other KVMs, PDUs and UPS systems.

Its unique 1U design allows for a one-person installation. The rail assembly sits directly on the rack mounting bracket, and allows the user to test how the console should be mounted within the rack before finally gliding the console onto the rail assembly.

The console and its floating OSD (on-screen-display) provides the convenience for IT personnel or network administrators to control and monitor data center or server devices. Convenient controls provide adjustments for auto tuning, brightness, contrast, color and image position for the video display. The ability to display the menu in English, German, French, Italian and Spanish further enhances the flexibility of the console

The Minuteman LCD consoles virtually eliminate the requirement for any desktop monitors as with traditional KVM installations.

The console system is constructed with heavy gauge sheet metal ensuring protection against accidental dents, damage and vibrations.



Minuteman® IU 15-inch single-rail rackmount LCD console (top) with:

- Minuteman Endeavor UPS
- Minuteman EnterprisePlus UPS
- Two Minuteman PDU units

Single-rail 15-inch LCD monitor benefits

- **Lower cost, 1U space-saving integrated keyboard/video monitor/mouse design preserves server room space**
- **Single-rail glide design enables smooth, effortless drawer operation**
- **Unique single-rail design allows one-person installation of the console**
- **Rackmounting kits included**
- **Two-year warranty** - Includes parts and labor (in U.S.A. and Canada only).

Specifications

Item	Description
LCD size	15-inch TFT active matrix
Resolution	1024 x 768 (XGA)
Pixel pitch	0.297mm x 0.297mm
Display colors	16.2 million – true color
Brightness	250 cd/m ² typical
Viewing angle	140 degree H x 120 degree V
Contrast ratio	300:1 typical
Keyboard	105-key PS/2 notebook keyboard with integrated touch pad and window key
Numeric key pad	Yes
Dimensions - closed	19.0in x 17.6in x 1.7in (482.6mm x 447.0mm x 43.2mm)
LCD panel functions	Soft power off/on, auto synchronize, scroll up, scroll down



Para Systems, Inc./Minuteman UPS
 1455 LeMay Drive, Carrollton, TX 75007 U.S.A.
 Phone 800.238.7272 +1 972.446.7363 Fax +1 972.446.9011



© Copyright 2007, Para Systems, Inc. Product specifications are subject to change without notice.
 Minuteman® is a registered trademark of Para Systems, Inc.

www.minutemanups.com • www.sizemyups.com • www.sizemypdu.com • www.comparemyups.com