

# PROLINE

## SILICONE FILLED WIRE CONNECTORS



### **KING 4 YELLOW - PROLINE WIRE CONNECTORS**

<u>CATALOG #</u>	<u>DESCRIPTION</u>	<u>SELLING UNIT</u>	<u>SPECIFICATIONS</u>
<b>10444</b>	Yellow	Bag of 10	Max. Voltage: 600-1000V Size: 1 1/16" x 1 9/16" Wire Combinations: Copper/Copper Wire Range: Min #18/ Max #12 Temperature Rating: 75°C (167° F) Sealant Temp: -45° F to 400° F



**KING 4 YELLOW**



### **KING 5 RED - PROLINE WIRE CONNECTORS**

<u>CATALOG #</u>	<u>DESCRIPTION</u>	<u>SELLING UNIT</u>	<u>SPECIFICATIONS</u>
<b>10555</b>	Red	Bag of 10	Max. Voltage: 600-1000V Size: 1 3/16" x 1 3/4" Wire Combinations: Copper/Copper Wire Range: Min #14 / Max #10 Temperature Rating: 75°C (167° F) Sealant Temp: -45° F to 400° F



**KING 5 RED**

# PROLINE

## PROLINE WIRE COMBINATIONS

### KING 4 YELLOW - WIRE COMBINATIONS

#### 600V

4-5 #18	3 #16 w/1 #18	2 #12 w/1 #16, 18 or 20
3-5 #16	1 #14 w/1-3 #16 or 18	1 #10 w/1 #14
2-4 #14	2 #14 w/1-2 #16 or 18	
2 #12	3 #14 w/1 #16 or 18	
2 #16 w/2 #18	1 #12 w/1 #14, 16, 18 or 20	



KING 4 YELLOW

### KING 5 RED - WIRE COMBINATIONS

#### 600V

2-5 #14	1 #12 w/1-4 #14	1 #10 w/1-3 #14
2-4 #12	2 #12 w/1-2 #14, 16 or 18	1 #10 w/1-2 #12
2 #10	3 #12 w/1-2 #16 or #18	2 #10 w/1 #14
1 #12 w/2-4 #16	3 #12 w/1 #14	



KING 5 RED