

Double Jacketed Buried Service Wire

WITH ALUMINUM SHIELD

Spec. 4287



Nominal Cable Data

CATALOG NUMBER	PAIRS AWG	O.D. (INCHES)	WEIGHT (LBS/MFT)	STANDARD LENGTH (FT)
2095138	2/22	0.33	48	1000
2095125	2/22	0.33	48	2500
2095126	2/22	0.33	48	5000
2095127	3/22	0.35	56	2500
2095128	3/22	0.35	56	5000
2095137	6/22	0.41	82	1000
2095129	6/22	0.41	82	2500
2095130	6/22	0.41	82	5000
2095131	2/24	0.30	39	2500
2095132	2/24	0.30	39	5000
2095133	3/24	0.32	46	2500
2095134	3/24	0.32	46	5000
2095135	6/24	0.37	64	2500
2095136	6/24	0.37	64	5000

Data subject to change without notice. Contact your Customer Service Representative for latest information.

Product Construction:

Conductors:

- Solid annealed copper

Insulation:

- High density polyethylene

Pairing:

- Varying pair lays

Core Filling:

- 80°C filling and flooding compounds

Inner Jacket:

- Linear low density polyethylene

Shield:

- Polymer-coated 0.008" aluminum tape

Rip Cord:

- Under the outer jacket

Outer Jacket:

- Black, linear low density polyethylene

Application:

- Intended for use in buried service application to the subscriber loops

Compliance:

- ICEA S-86-634

Packaging:

- Standard coils or on non-returnable plywood reels in lengths as shown above