

Glass Supported Drop Wire 2, 3 and 6 Pair

BELL SYSTEM TYPE AND RUS (REA)

Spec. 4292-4294

Product Construction:

Conductors:

- 22 AWG solid annealed copper

Insulation:

- Color-coded high density polyethylene

Assembly:

- 2, 3 or 6 twisted pairs and rip cord placed parallel between the glass strength members

Jacket:

- Black, flame-retardant, weather- and abrasion-resistant PVC compound extruded over core assembly

Application(s):

- Self-supporting drop wire intended for aerial service connection to the subscriber
- Compatible with "P" Clamp/Wedge type hardware
- Glass strength member is lightweight, easy to install
- No need for support wire grounding
- Not affected by salt air and corrosive environments

Compliance:

- Telcordia (Bellcore) Specification TR-NWT-001069
- Rural Utilities Service (RUS) Bulletin 1753 F-204

Packaging:

- Available in Pull-Pac™ cartons (PP), coils (CL), reels (RL) and reelsaver (RS)



Nominal Cable Data

CATALOG NUMBER	PAIRS AWG	O.D. (INCHES)	WEIGHT (LBS/MFT)	STANDARD LENGTH (FT)
2090008*	2/22	0.20 x 0.40	40	750 PP
2090010	2/22	0.20 x 0.40	40	1000 CL
2090012	2/22	0.20 x 0.40	40	750 CL
2090021	2/22	0.20 x 0.40	40	500 RS
2090053	2/22	0.20 x 0.40	40	3500 (28") RL
2090052*	3/22	0.28 x 0.44	54	600 PP
2090013	6/22	0.27 x 0.50	80	3500 (30") RL
2090014	6/22	0.27 x 0.50	80	400 CL
2090018*	6/22	0.27 x 0.50	80	400 PP

Data subject to change without notice. Contact your Customer Service Representative for latest information.

* These OVD wire items have sequential markings.