

Clamp Ties

The clamp tie has triangular shaped tabs extending beneath the head, allowing for optimal surface contact and complete circumferential compression to 360 degrees. The clamps are recommended for soft rubber hose applications, as well as for fuel, water, and air vacuum lines. Clamp ties are manufactured in natural and heat stabilized, high impact, black nylon 6/6.



Clamp Ties						
Hellermann Tyton Part No.	Min. Tensile Strength (lbs.)	Maximum Bundle Dia. In. (mm.)	Approx. Length In. (mm.)	Approx. Width In. (mm.)	Pkg. Qty.	Hellermann Tyton Installation Tools
CTT20R9C2 CTT20R9M4	20	7/8" (22.2)	4" (101.6)	.09" (2.2)	100 1000	TWT1, MK3P, MK7, MK7P, MK9
CTT60R9C2 CTT60R9M4	60	1-3/4" (44.4)	8" (203.2)	.18" (4.6)	100 1000	TWT1, MK3P, MK6PN, MK7, MK7P, MK9
CTT60L9C2 CTT60L9M4	60	4" (101.6)	15" (381.0)	.18" (4.6)	100 1000	

Ties listed above are natural. Contact HellermannTyton for heat stabilized, high impact, black nylon 6/6 information.

Kabelrap Bundling System

- Very high bundling strength
- Particularly resistant to salt water, oils, greases, and hydraulic fluids
- Material - Weather resistant, nylon 6/6, black
- Special, **required** hand tool shown upper right Part No. 121-00680



Required Tool –
121-00680



Kabelrap
Application



Kablerap Bundling System

HellermannTyton Part No.	Material/ Color	Min. Tensile Strength (lbs.)	Maximum Bundle Dia. In. (mm.)	Approx. Length In. (mm.)	Approx. Width In. (mm.)	Pkg. Qty.	Required Installation Tool
121-61860	Weather Resistant, Nylon 6/6, Black	110	1-1/2" (39)	7-1/4" (183)	.24" (6.0)	50	121-00680
121-63560		110	3-3/4" (93)	14" (356)	.25" (6.4)	50	
121-82160		175	1-3/4" (47)	8-1/4" (210)	.31" (8.0)	50	
121-83360		175	3-3/8" (86)	13-1/4" (337)	.31" (8.0)	50	