

Minuteman[®] EnSpire[™] Standby UPS Series Uninterruptible Power Supply

EN400 - 400VA/200W EN600 - 600VA/300W

EnSpire EN600 - 600VA/300W

Standby UPS

The Minuteman® EnSpire[™] Series UPS is an exciting new UPS line that provides the features needed to protect your valuable equipment in a low-cost product.

Each unit has six outlets, three provide battery support along with spike and surge protection only and three with spike and surge protection only. In addition, two of the outlets are specifically spaced to support transformer blocks.

The EnSpire UPS has a small footprint and is uniquely designed with outlets on the top for placement on or under a desk or table and both models can be wall mounted.

For over 25 years, Para Systems, Inc. has provided quality power products and excellent personalized service with direct human response to all service and support calls. EnSpire products pass extensive quality control before being shipped to our end users.

Applications

- Small capacity equipment loads
- Desktop/laptop workstations
- Small key systems
- VoIP handsets
- Digital audio/video systems
- Low-power network devices


* Excludes lead acid batteries

EnSpire Features

- USB Communications EnSpire UPS USB connections are automatically recognized by Microsoft Windows® software. No special USB drivers are required. The EnSpire Series automatically recognizes USB connections with its HID (Human Interface Device)compliant USB communications.
- Minuteman SentryPlus Software SentryPlus auto-shutdown and monitoring software is included with every unit. No special downloads or coupons are required.
- Telephone/Fax/Modem Line Protection The EnSpire UPS provides a low cost means of protecting telephone/fax/modem lines.
- RoHS Compliant All EnSpire products are manufactured using non-hazardous* materials making them safer for the environment.
- Larger Load Capacities Minuteman has increased the capacities of the units allowing them to support larger power requirements.
- Minuteman Support Para Systems includes full end user support that includes toll-free technical service from our headquarters in Carrollton, Texas.
- Warranty The UPS is covered by a threeyear parts and labor warranty and \$50,000 Minuteman Platinum Protection Plan® (U.S.A. and Canada only). The battery is covered by a two-year warranty.

Minuteman[®] EnSpire[™] Series Standby UPS Specifications

| System Specifications | | | |
|-----------------------------|---------------------------------|---|--|
| Model Number | EN400 | EN600 | |
| Maximum Power Capacity | 400VA / 200W | 600VA / 300W | |
| Тороlоду | St | Standby UPS | |
| | Input | | |
| Nominal Frequency | 50 or 60H | 50 or 60Hz, ±5Hz, autosensing | |
| Voltage Range | 9 | 96 - 146VAC | |
| Low Voltage Transfer Point | 96V (± 3%) resets to util | 96V (± 3%) resets to utility power at 101V (± 3%) or higher | |
| High Voltage Transfer Point | 146V (± 3%) resets to ut | 146V (± 3%) resets to utility power at 140V (± 3%) or lower | |
| Surge Energy Rating | | 320 J | |
| Input Protection | Resetta | Resettable circuit breaker | |
| | Output Non-Battery Operation | | |
| Voltage Range | 120VA | 120VAC: 100 - 140VAC | |
| Frequency Range | 60Hz: 55 - 6 | 60Hz: 55 - 65Hz or 50Hz: 45 - 55Hz | |
| | Output Battery Operation | | |
| Waveform Type | Simul | Simulated sine wave | |
| Nominal Voltage | | 120VAC | |
| Voltage Regulation | Nominal ±5% (u | Nominal ±5% (until Low Battery Warning) | |
| Frequency | 50/60Hz, ±0.5Hz (u | 50/60Hz, ±0.5Hz (unless synchronized to utility) | |
| Transfer Time | | 6-8 ms Typical | |
| Overload Capacity | 105% for 10-seconds | 105% for 10-seconds, 115% Shutdown Immediately | |
| Protection | Over-Current, Short-Circui | Over-Current, Short-Circuit Protected and Latching Shutdown | |
| | Physical | | |
| Size - Net L x W x H | 11.97 x 4.84 x 3. | 11.97 x 4.84 x 3.35 in (304 x 123 x 85 mm) | |
| Weight - Net | 6.44 lb (2.92 kg) | 7.05 lb (3.20 kg) | |
| Size - Shipping L x W x H | 15.0 x 8.20 x 5.4 | 15.0 x 8.20 x 5.43 in (380 x 208 x 138 mm) | |
| Weight - Shipping | 8.00 lb (3.30 kg) | 8.00 lb (3.60 kg) | |
| | Regulatory Compliance | | |
| Safety Approvals, EMC | UL1778, cUL (CSA | UL1778, cUL (CSA 22.2 no. 107.1), FCC Class B | |



www.minutemanups.com • www.sizemyups.com • www.sizemypdu.com • www.comparemyups.com