

COMODO

**MODERN DESIGN
HIGH TECH
MODEST COST**



TRI Composite tapered MDF cabinets—less resonance and reduced standing waves.

Bravox Titanium injected cone drivers—fast, rigid and light.

Ferrofluid, Rare earth Neodymium, coated textile dome VIFA tweeters with heat sinks—Frequency beyond 30KHz. Truncated face plate exhibits true waveguide loading.

Individual grille cut outs for each driver port.

Magnetic fasteners with neoprene dampening.

Design of the baffle, grille and tweeter allow the tweeter to perform to its full potential with none of the inherent problems of conventional cabinet design.

LINKWITZ-RILEY cross over—superior driver control and 12 db slopes.

16 AWG internal wire, air core coils, poly caps higher frequencies, better stability, lower loss, higher resistance.



COMODO S: Bookshelf



- Nominal Impedance: 4 ohms
- Sensitivity: 86db
- Min. Power Requirement: 10 Watts RMS
- Frequency Range: 65Hz-30KHz
- Finish: Black ash
- Weight: 4.4 Kg
- Dimensions: 30.9 H x 18 W x 24 D (cm)
12-1/4 x 7-1/8 x 9-1/2 (in)

COMODO F: Floorstanding



- Nominal Impedance: 6 ohms
- Sensitivity: 87db
- Min. Power Requirement: 15 Watts RMS
- Frequency Range: 50Hz-30KHz
- Finish: Black ash
- Weight: 9 Kg
- Dimensions: 90.3 H x 18 W x 24 D (cm)
35-1/4 x 7-1/8 x 9-1/2 (in)



Rigid Titanium Woofers



Spikes and picks included



Surface mount Tweeters



5way Binding Posts

ANGSTROM LOUDSPEAKERS MC

391 Marwood Drive, Unit 6
Oshawa, ON, L1H 7P8
Tel: 416-988-8806
E-mail: info@angstromloudspeakers.com
www.angstromloudspeakers.com

Visit all
Of our
models

