

D.

DEFINITIVE TECHNOLOGY



Mythos LCR On-Wall Speaker

The Mythos® Series LCR on-wall speakers elevate home theater experiences indoors and out. Offering horizontal or vertical wall-mountable solutions for the left, center, or right channel, these low-profile speakers blend high-performance sound and designer aesthetics in a weather-protected, adjustable, rigid aluminum enclosure. Mythos Series LCR speakers are available in three models.

KEY BENEFITS

Slim Profile and Luxury Finishes

Ultra-slim cabinet measures less than 2" deep and features clean, modern aesthetics; refined anodized aluminum finishes; and horizontal or vertical wall-mount compatibility. Symmetrically adjustable extensions expand up to 3.5" to aesthetically frame 65", 75", or 85"-class and larger television displays, for a flush look and a streamlined appearance alongside and under your TV.

Acoustically Optimized Cabinet

A highly rigid, tuned, aircraft-grade aluminum enclosure ensures the truest sound, uncolored by cabinet resonances, for pristine sonic reproduction.

IP66-Rated Weather Protection

Water- and dust-resistant construction means you can enjoy stunning home theater sound and high-resolution music outdoors.

Multi-Driver Arrays

Mythos LCR on-wall speakers feature two- and three-way driver arrays. Multiple-driver arrays improve driver performance and project robust, expansive sound over a wide area. Add a subwoofer for full-range sound.

XTDD Drivers

Ultra-stiff, 3.5" anodized aluminum dome woofers and midrange drivers eliminate breakup and broaden dispersion, for crisp, clear sound and a spacious, enveloping soundstage.

Aluminum Oxide Dome Tweeter

A 1", rigid, well-damped Dymension™ Series tweeter delivers smooth extended response, crisp transients, and pinpoint imaging, for cohesive, lifelike sound that draws you inside the action.

Timbre-Matched

Consistent sound across Definitive Technology speakers gives you the flexibility to mix and match speakers to build the ultimate system or a starter system that can expand as your needs grow.

PRODUCT FEATURES

- On-wall LCR home theater speakers blend premium sound and designer aesthetics
- IP66-rated weather-resistant design is suitable for use outdoors
- 3.5" XTDD woofers and midrange drivers produce balanced lows and mids
- 1" aluminum oxide dome tweeter delivers precise highs, vivid realism
- Precision crossovers optimize drivers for accurate, lifelike sound
- Mount vertically or horizontally (mount included) for a seamless system look
- Timbre-matched for cohesive sound alongside Definitive Technology speakers

LCR-85



LCR-75



LCR-65



Mythos® LCR On-Wall Speaker

SPECIFICATIONS			
	LCR-65	LCR-75	LCR-85
Dimensions (H × D)	6.25 × 1.87 in. (159 × 48 mm)	6.25 × 1.87 in. (159 × 48 mm)	6.25 × 1.87 in. (159 × 48 mm)
Adjustable Width (W)	32.6 × 36 in. (828 × 914 mm)	37.7 × 41.1 in. (958 × 1047 mm)	41.8 × 45.2 in. (1062 × 1148 mm)
Symmetrically Adjustable Extensions	3.42 in. (87 mm)	3.42 in. (87 mm)	3.42 in. (87 mm)
Weight	10 lbs (4.3 kg)	12 lbs (5.5 kg)	14 lbs (6.18 kg)
Color / Material	Black anodized aluminum	Black anodized aluminum	Black anodized aluminum
Grille Material	Micro-perforated powder-coated steel	Micro-perforated powder-coated steel	Micro-perforated powder-coated steel
Tweeter	(1) 1 in. aluminum oxide dome	(1) 1 in. aluminum oxide dome	(1) 1 in. aluminum oxide dome
Midrange	–	(2) 3.5 in. XTDD aluminum dome	(2) 3.5 in. XTDD aluminum dome
Woofer	(4) 3.5 in. XTDD aluminum dome	(4) 3.5 in. XTDD aluminum dome	(6) 3.5 in. XTDD aluminum dome
Number of Channels	1	1	1
Frequency Response	100 Hz–25 kHz (-10dB) 120 Hz–20 kHz (-3dB)	100 Hz–25 kHz (-10dB) 120 Hz–20 kHz (-3dB)	100 Hz–25 kHz (-10dB) 120 Hz–20 kHz (-3dB)
Nominal Impedance	4Ω (8Ω compatible)	4Ω (8Ω compatible)	4Ω (8Ω compatible)
Sensitivity	88dB (2.83V/1m)	88dB (2.83V/1m)	88dB (2.83V/1m)
Recommended Amplifier Power	60W	60W	60W
IP Rating (Ingress Protection)	IP66	IP66	IP66
Warranty	5-year	5-year	5-year
Included Accessories	(1) Wall-mount bracket	(1) Wall-mount bracket	(1) Wall-mount bracket

