1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 921003

DESCRIPTION: RG-6/U PLENUM COAXIAL CABLE WITH 95% COPPER BRAID

RATING: ETL LISTED AS CL2P and
C(ETL) CERTIFIED AS CMP FT6

Construction Parameters:

		Wall (in)*	OD (in)*
Conductors:	18 AWG (1/.040) Solid Copper		0.040
Dielectric:	Foam FEP color natural	0.065	0.170
Shielding:	95% Copper Braid		0.195
Jacket:	Low Smoke PVC	0.022	0.238

Electrical Properties:

Cable Cross-section:
(NOT TO SCALE)

		VALUE*
Conductor Resistance(ohms/kft):		6.5
Impedance (ohms):		75
Capacitance (pF/ft):		16.5
Velocity of Propagation (%):		82
Attenuation (db/100 ft):	50 MHz	1.5
	100 MHz	2.0
	200 MHz	3.0
	500 MHz	5.2
	700 MHz	6.0

Miscellaneous Information:

Jacket Color:	Natural
Jacket Print (Teal/Aqua): ASCENDING/DESCENDING FOOTAGE MARKING	COLEMAN CABLE 921003 18 AWG RG 6/U TYPE CL2P c(ETL)us 75 C 3020465 CMP FT6 WO# XXXXXX
Flame Rating:	UL 910 Steiner Tunnel Smoke and Flame Test CSA FT6 Horizontal Flame and Smoke Test
Temperature Rating:	75^{o} C
Applicable NEC Article:	725
Approx. Weight (lb/1000 ft):	43

This product complies with European Directive 2002/95/EC (RoHS)
On special orders the customer will accept all factory lengths and ± 10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise

Company Name: _____

Customer Approval: _____   Date: _____

Issued: 05/03/06

* = Nominal value
By: PEP